


SF34 Mono Color Silicone LED Linear Flex

SF34-48V-2835-96-CC-2200K-6500K-12W

Specification





Technical Parameters

Electrical	
Input Voltage	48V DC (Built In Constant Current)
Power Consumption	12W/m
Physical	
LED Count	96 LEDs/m
Cutting Unit	12 LEDs
Cutting Unit Length	125 mm
Minimum Bend Diameter	400mm
Output	
LED Light	Epistar SMD LED 2835
CRI	>80, >90
Max Run Length*	
Single Feed	53 M
Double Feed	106 M
Beam Angle	120°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C
Temperature Ranges	
Installation	0°C to 50°C
Operating	-40°C to 55°C
Dependability	


Optional Color	
	2200K(2238±102K)
	2500K(2460±120K)
	2700K(2725±145K)
	3000K(3045±175K)
	3500K(3465±245K)
	4000K(3985±275K)
	4500K(4503±243K)
	5000K(5209±283K)
	5700K(5667±355K)
	6500K(6532±510K)
	Green(520-530nm)
	Blue (455-465nm)
	Lemon Yellow (570-580nm)
	Pink (610-620nm)

IP Rating	IP68 Wet location submersible <2m
-----------	-----------------------------------

Illuminance Distribution



White Color Charts





SF34 Configuration and Accessories



Mold injection Connector (IP68 Factory Assembly Only)





Direct Entry Connector





Side Entry Connector




Bottom Entry Connector




End Cap





Jumper




SF34 Configuration and Accessories



Waterproof Interrupter



Male Connector



Female Connector

